



BDM 表:

序号	品名	料号	材料规格	电镀方式/颜色	使用数量	备注
4	0.5mm间距C型翻盖式下接-焊片	FPC050C009-4	Phosphor-Bronze T-0.20MM	镀锡	2 PCS	
3	0.5mm间距C型翻盖式下接-锁扣	FPC050C009-3Y	SEE TABLE 1	—	1 PCS	
2	0.5mm间距C型翻盖式下接-PIN	FPC050C009-2	Phosphor-Bronze T-0.20MM	镀锡	—	
1	0.5mm间距C型翻盖式下接-底座	FPC050C009-1NY	SEE TABLE 1	—	1 PCS	

TABLE 2:

Z	包装方式	Y	材质
1	管装	A	PA 46
2	盘装	B	LCP
3	袋装	C	PA 9T

TABLE 1:

N	A	B	C
4	1.50	2.60	5.70
5	2.00	3.10	7.20
6	2.50	3.60	8.70
7	3.00	4.10	10.20
8	3.50	4.60	11.70
9	4.00	5.10	13.20
10	4.50	5.60	14.70
11	5.00	6.10	16.20
12	5.50	6.60	17.70
13	6.00	7.10	19.20
14	6.50	7.60	20.70
15	7.00	8.10	22.20
16	7.50	8.60	23.70
17	8.00	9.10	25.20
18	8.50	9.60	26.70
19	9.00	10.10	28.20
20	9.50	10.60	29.70
21	10.00	11.10	31.20
22	10.50	11.60	32.70
23	11.00	12.10	34.20
24	11.50	12.60	35.70
25	12.00	13.10	37.20
26	12.50	13.60	38.70
27	13.00	14.10	40.20
28	13.50	14.60	41.70
29	14.00	15.10	43.20
30	14.50	15.60	44.70
31	15.00	16.10	46.20
32	15.50	16.60	47.70
33	16.00	17.10	49.20
34	16.50	17.60	50.70
35	17.00	18.10	52.20
36	17.50	18.60	53.70
37	18.00	19.10	55.20
38	18.50	19.60	56.70
39	19.00	20.10	58.20
40	19.50	20.60	59.70
41	20.00	21.10	61.20
42	20.50	21.60	62.70
43	21.00	22.10	64.20
44	21.50	22.60	65.70
45	22.00	23.10	67.20
46	22.50	23.60	68.70
47	23.00	24.10	70.20
48	23.50	24.60	71.70
49	24.00	25.10	73.20
50	24.50	25.60	74.70
51	25.00	26.10	76.20
52	25.50	26.60	77.70
53	26.00	27.10	79.20
54	26.50	27.60	80.70
55	27.00	28.10	82.20
56	27.50	28.60	83.70
57	28.00	29.10	85.20
58	28.50	29.60	86.70
59	29.00	30.10	88.20
60	29.50	30.60	89.70

额定电流 Current rating: 0.4A  
 额定电压 Voltage rating: 50V  
 耐电压 Withstand voltage: 200V AC/ml nute  
 接触电阻 Contact resistance:  $\leq 20m\Omega$   
 绝缘电阻 Insulation resistance: 500M $\Omega$   
 工作温度 Working temperature: -20° C ~ +80° C



碩方電子科技股份有限公司

DRAWN BY	CHECKED BY	APPROVED BY	ITEM	PART NO	TOLERANCE	ANGLE PROJECTION	UNIT	SCALE	DATE	REVISION	DESCRIPTION	DATE
			0.5mm间距C型翻盖式下接 (0.5S-CX-nPWB)	FPC050C009-NVZ		$\times \pm 0.2$ $, \times \pm 0.10$	mm	1:1	2010/03/31		新订图面	2010/03/31