

GM-5157

Ultra-High Performance

GNSS Smart Antenna Module

Overview

GM-5157 is a thin, compact, easy to use, high performance low power GPS smart antenna module with patch antenna for various location and timing applications. GM-5157 supports multiple satellite positioning systems – GPS, QZSS and SBAS ranging.

Based on our experienced design, GM-5157 fully exhibits the excellent performance of MT3337 chip. It works in GPS signal difficult environment, provides fast acquisitions and excellent tracking performance.

Applications

- Driving recorder
- Automatic vehicle location
- Vehicle navigation device
- Marine GPS plotters
- Timing (GPS clock, FEMTO cell, traffic lights etc.)

Features

- Compact and thin – 15 x 15 x 6.5 (mm)
- High performance: -165dBm tracking sensitivity
- Low power: 21 mA at continuous tracking
- GPS/QZSS/SBAS support
- SBAS (WAAS, EGNOS, MSAS, GAGAN) support
- AGPS – up to 30-day orbit predictions from server
- 12 multi-tone active interference cancellers
- Indoor/outdoor multi-path detection & compensation
- Up to 5Hz update rate¹
- High accuracy 1PPS timing
- Easy to use: built-in patch antenna & 6-pin wire to

RoHS
Compliant



board connector

- V_BAT pin support for faster position fix
- Green LED for position fix indication
- Fully EMI shielded
- Industrial operating temperature range: -40 ~ 85°C

Notes

1. Some features need special firmware or command programmed by customer
2. MOQ-based customization is welcome.

Technical Specifications

Receiver Performance Data

Receiver Type	GNSS Chipset: MT3337 GPS, QZSS: L1 1575.42MHz C/A code: 1.023 MHz chip rate Channels: Tracking: 22 /acquisition: 66
Horizontal Position Accuracy	< 3.0m (Autonomous) < 2.5m (WAAS) (50% 24hr static, -130dBm)
Velocity Accuracy	<0.1 m/s (speed, w/o SBAS) <0.05 m/s (speed w/ SBAS) (50% @30m/s)
Timing Accuracy	±10ns RMS (1PPS output)
Time To First Fix	Autonomous Hot start <1sec, average Warm start <35sec, average Cold start <35sec, average Reacquisition (50% -130dBm)

Navisys Technology Corp.

Tel : +886-3-5632598

Sales contact: sales@navisys.com.tw

Address: 2F, No.56, Park Ave. II, Science-Based Industrial Park, Hsinchu 300, Taiwan (R.O.C.)

<http://www.navisys.com.tw/>

Fax: +886-3-5632597

Technical support: service@navisys.com.tw

Sensitivity (Autonomous)	-148dBm (acquisition) -165dBm (tracking)
Update Rate ⁺	Up to 5Hz, default 1Hz
Max. Altitude ⁺	<18,000 m
Max. Velocity	<1,852 km/hr
Datum ⁺	WGS-84(default)
Protocol Support ⁺	NMEA 0183 V3.01, MTK NMEA 4800/9600(default)/38400/115200bps N,8,1(No parity, 8 data bits, 1 stop bit); Default: GGA, GSV, GSA, RMC, @1Hz
SBAS Support	WAAS, EGNOS, MSAS, GAGAN
Dynamics	<4g

⁺Please contact Navisys for any customization demand.


Electrical Data

Power Supply	3 ~ 4.3 V
Power Consumption	21mA / average tracking
Backup Power (V_BAT)	2.1 ~ 4.2 V Power consumption: 8uA
TTL I/O	V _{IH} : 2.1~3.1V, V _{IL} : 0~0.7V V _{OH} : ≥2.38V, V _{OL} ≤0.42V
Protocols	NMEA, MTK NMEA


Environmental Data

Operating temperature	-40 ~ 85°C
Storage temperature	-40 ~ 85°C
Vibration	5Hz to 500Hz, 5g
Shock	Half sine 30g/11ms

Mechanical Data: 15 x 15 x 6.5 (mm)



6-pin Interface, pitch 0.8mm



GM-5157A

Pin	Name	Function	I/O
1	GND	Ground	Input
2	VCC	Power supply	Input
3	TXD	TTL level serial data output (from GPS)	Output
4	RXD	TTL level serial data input (to GPS)	Input
5	1PPS	Time Pulse Per Second	Output
6	V_BAT	Backup power	Input

Ordering Information

GM-5157X

X=A	9600bps, GGA, GSV, GSA, RMC@1Hz
-----	------------------------------------

*This document is subject to change without notice.