



- 备注:
1. 外壳材料: 铁料 (SPCC) 外表面镀锌
  2. 主体材料: LCP 胶料
  3. 端子材料: 青铜 (C2680) 接触点镀金1U,

- NOTE :
- 1.SPECIFICATION:
    - 1.1.CURRENT RATING: 0.5 Amp Max.
    - 1.2.VOLTAGE RATING: 40 V ac(r.m.s) Max.
    - 1.3.CONTACT RESISTANCE: 10m ohms Max.mated
    - 1.4.INSULATION RESISTANCE:100M ohms Min.
    - 1.5.DIELECTRIC WITHSTANDING VOLTAGE: AC 500V Min. (for 1 minute)
    - 1.6.OPERATION TEMPERATURE RANGE: -25°C~85°C
  - 2.MECHANICAL
    - 2.1 INSERTION FORCE: 4.5KGF MAXMUM
    - 2.1 WITHDRAWAL FORCE:1.0KGF MINIMUM; 4.0KGF MAXMUM

公差一览表 TOLERANCE UNLESS OTHERWISE				单位 UNITS	MM	制图 DRAWING	客户料号 CUSTOMER PART NO.	HDMI--19P公头(新)	
X	±0.15	X'	±5°	比例 SCALE	1:	审核 CHKD	产品名称 PRODUCT NO.	角法 VIEW	原本 VER
.X	±0.10	.X'	±2°						
XX	±0.08	XX'	±1°	日期 DATE	2007/11/26	核准 APPD			
.XXX	±0.03	.XXX'	±0.5°						